

US Application No. 09/558,532

ATTY DOCKET NO. 10990616-1

Page 2

(c) evaluating a performance characteristic of the deposition apparatus based on the detected signals

wherein the sensing element optionally comprises the substrate;  
additionally comprising:

when after the dispensing of some droplets onto the substrate an error is detected in which an evaluated performance characteristic is outside a predetermined tolerance, then the source of the error is corrected prior to dispensing of other of the droplets onto that same substrate or the deposition apparatus is operated so as to compensate for the error during dispensing of other of the droplets onto that same substrate.

5. A method according to claim 4 wherein the error is detected after the dispensing of some of the droplets for an array, and the source of the error is corrected prior to dispensing of other of the droplets for the same array or the deposition apparatus is operated so as to compensate for the error during dispensing of other of the droplets for the same array.

6. A method according to claim 4 wherein:  
multiple arrays are fabricated on the same substrate; and  
wherein the error is detected after the dispensing of droplets for at least one of the arrays on the same substrate, and the source of the error is corrected prior to dispensing of droplets for other of the arrays on the same substrate or the deposition apparatus is operated so as to compensate for the error during dispensing of droplets for the same array or other of the arrays on the same substrate.

7. (TWICE AMENDED) A method of fabricating at least one addressable array of biopolymers with multiple features on a substrate using a drop deposition apparatus having a drop dispenser unit and a sensing element, comprising:

(a) for each of multiple addresses, dispensing droplets carrying the biopolymers or biopolymer precursors from a drop dispenser unit onto the sensing element, and onto the substrate so as to fabricate the array;

US Application No. 09/558,532

ATTY DOCKET NO. 10990616-1

Page 3

(b) detecting electrical signals resulting from dispensed droplets striking the sensing element;

(c) evaluating a performance characteristic of the deposition apparatus based on the detected signals;

wherein the sensing element optionally comprises the substrate;

32X  
cmx  
additionally comprising changing biopolymers or biopolymer precursors in the dispenser unit to different biopolymers or biopolymer precursors, wherein the detection and evaluation are performed after the changing and before a dispensing of any droplets for an array.

---

9. A method according to claim 4 wherein the dispenser unit comprises a pulse jet which ejects a droplet in response to a signal and which can de-prime, and the error is corrected by re-priming the pulse jet.

---

10. (TWICE AMENDED) A method of fabricating at least one addressable array of biopolymers with multiple features on a substrate using a drop deposition apparatus having a drop dispenser unit and a sensing element, comprising:

33  
(a) for each of multiple addresses, dispensing droplets carrying the biopolymers or biopolymer precursors from a drop dispenser unit onto the sensing element, and onto the substrate so as to fabricate the array;

(b) detecting electrical signals resulting from dispensed droplets striking the sensing element;

(c) evaluating a performance characteristic of the deposition apparatus based on the detected signals;

wherein the sensing element optionally comprises the substrate;

additionally comprising when an error is detected in which an evaluated performance characteristic is outside a predetermined tolerance, identifying one or more features on the array which are defective as a result of the error.

---

11. (PREVIOUSLY AMENDED) A method according to claim 10 additionally comprising communicating an identity of the identified defective features to a remote location or saving such information onto a storage medium.

US Application No. 09/558,532

ATTY DOCKET NO. 10990616-1

Page 4

13. (AMENDED) A method of fabricating at least one addressable array of biopolymers with multiple features on a substrate using a drop deposition apparatus having a drop dispenser unit and a sensing element, comprising:

- B<sub>4</sub>
- (a) for each of multiple addresses, dispensing droplets carrying the biopolymers or biopolymer precursors from a drop dispenser unit onto the sensing element, and onto the substrate so as to fabricate the array;
  - (b) detecting electrical signals resulting from dispensed droplets striking the sensing element;
  - (c) evaluating a performance characteristic of the deposition apparatus based on the detected signals

wherein the sensing element optionally comprises the substrate;

and wherein:

the dispenser unit comprises one or more pulse jets which eject a droplet in response to a signal which require priming; and

the evaluated performance characteristic is whether one or more of the pulse jets are primed prior to dispensing any droplets for an array.

14. A method according to claim 13 additionally comprising, when an error is detected in which at least one of the pulse jets is not primed, then firing the pulse jet one or more times until the detected electrical signals indicate the pulse jet is primed.

15. (TWICE AMENDED) A method of fabricating at least one addressable array of biopolymers with multiple features on a substrate using a drop deposition apparatus having a drop dispenser unit and a sensing element, comprising:

- B<sub>5</sub>
- (a) for each of multiple addresses, dispensing droplets carrying the biopolymers or biopolymer precursors from a drop dispenser unit onto the sensing element, and onto the substrate so as to fabricate the array;
  - (b) detecting electrical signals resulting from dispensed droplets striking the sensing element;
  - (c) evaluating a performance characteristic of the deposition apparatus based on the detected signals

US Application No. 09/558,532

ATTY DOCKET NO. 10990616-1

Page 5

wherein the sensing element optionally comprises the substrate;

and wherein:

the dispenser unit is repeatedly scanned across the substrate while dispensing droplets so as to fabricate the array;

the sensing element is struck by droplets so as to generate electrical signals when the dispenser unit passes beyond the array being fabricated on multiple scans during fabrication of the array.

16. (PREVIOUSLY AMENDED) A method according to claim 15 wherein the sensing element is struck by droplets so as to generate electrical signals when the dispenser unit passes beyond the array being fabricated on each of multiple scans during fabrication of the array.

17. (AMENDED) A method of fabricating at least one addressable array of biopolymers with multiple features on a substrate using a drop deposition apparatus having a drop dispenser unit and a sensing element, comprising:

- (a) for each of multiple addresses, dispensing droplets carrying the biopolymers or biopolymer precursors from a drop dispenser unit onto the sensing element, and onto the substrate so as to fabricate the array;
- (b) detecting electrical signals resulting from dispensed droplets striking the sensing element;
- (c) evaluating a performance characteristic of the deposition apparatus based on the detected signals;

wherein the sensing element optionally comprises the substrate;

and wherein the sensor comprises the substrate.

21. (AMENDED) A method of fabricating at least one addressable array of biopolymers with multiple features on a substrate using a drop deposition apparatus having a drop dispenser unit and a sensing element, comprising:

- (a) for each of multiple addresses, dispensing droplets carrying the biopolymers or biopolymer precursors from a drop dispenser unit onto the sensing element, and onto the substrate so as to fabricate the array;

US Application No. 09/558,532

ATTY DOCKET NO. 10990616-1

Page 6

- (b) detecting electrical signals resulting from dispensed droplets striking the sensing element;
- (c) evaluating a performance characteristic of the deposition apparatus based on the detected signals

wherein the sensing element optionally comprises the substrate;

and wherein the evaluated performance characteristic is the velocity of droplets dispensed from the drop dispenser unit;

the method additionally comprising dispensing multiple droplets from the dispenser unit at each of at least two different distances from the sensor, and wherein droplet velocity is evaluated based on the phase difference between the detected signal from multiple droplets at each distance.

28. An apparatus for fabricating at least one addressable array of biopolymers on a substrate, comprising:

(a) a drop dispensing unit which can deposit droplets carrying the biopolymers or biopolymer precursors onto different addresses on the substrate so as to fabricate the array;

(b) a sensing element and amplifier to detect electrical signals resulting from dispensed droplets striking the sensing element;

(c) a processor which:

causes the drop dispensing unit to dispense droplets toward the sensing element after the dispensing of some droplets onto the substrate and evaluates a performance characteristic of the dispensing unit based on the resulting detected signals; and

when an error is detected in which an evaluated performance characteristic is outside a predetermined tolerance then the processor, prior to causing the drop dispenser to dispense droplets onto that same substrate, activates an operator alert or operates the apparatus so as to correct for the error before, or compensate for the error during, dispensing of other of the droplets onto that same substrate.

29. An apparatus according to claim 28 wherein:

US Application No. 09/558,532

ATTY DOCKET NO. 10990616-1

Page 7

the processor causes the drop dispensing unit to dispense droplets toward the sensing element after dispensing of some droplets for an array; and

when the error is detected the processor activates the operator alert or operates the apparatus so as to correct for the error before, or compensate for the error during, dispensing of the other droplets for that same array.

---

30. (AMENDED) An apparatus according to claim 28 wherein:

the processor causes the drop dispensing unit to dispense droplets so as to form multiple arrays on the same substrate, and to dispense droplets toward the sensing element after dispensing some of the droplets for the arrays on the same substrate;

when the error is detected the processor operates the apparatus so as to correct for the error before, or compensate for the error during, dispensing of the other droplets for other of the arrays on the same substrate.

---

31. (PREVIOUSLY AMENDED) An apparatus for fabricating at least one addressable array of biopolymers with multiple features on a substrate, comprising:

(a) a drop dispensing unit which can deposit droplets carrying the biopolymers or biopolymer precursors onto different addresses on the substrate so as to fabricate the array;

(b) a sensing element and amplifier to detect electrical signals resulting from dispensed droplets striking the sensing element;

(c) a processor which:

causes the drop dispensing unit to dispense droplets toward the sensing element after the dispensing of some droplets onto the substrate and evaluates a performance characteristic of the apparatus based on the resulting detected signals; and

when an error is detected in which an evaluated performance characteristic is outside a predetermined tolerance, identifies one or more features on the array which are defective as a result of the error.

US Application No. 09/558,532

ATTY DOCKET NO. 10990616-1  
Page 8

32. (PREVIOUSLY AMENDED) An apparatus according to claim 31 wherein the processor additionally communicates an identity of the identified defective features to a remote location or saves such information onto a storage medium.

38. (AMENDED) An apparatus for fabricating at least one addressable array of biopolymers on a substrate, comprising:

- B9
- (a) a drop dispensing unit which can deposit droplets carrying the biopolymers or biopolymer precursors onto different addresses on the mounted substrate so as to fabricate the array;
  - (b) a sensing element and amplifier to detect electrical signals resulting from dispensed droplets striking the sensing element;
  - (c) a processor which causes the drop dispensing unit to dispense droplets toward the sensing element and which evaluates a performance characteristic of the apparatus based on the resulting detected signals, wherein the evaluated performance characteristic is the velocity or placement of droplets;

wherein the processor causes the dispenser unit to dispense multiple droplets at each of at least two different distances from the sensor, and wherein droplet velocity is evaluated based on the phase difference between the detected signal from multiple droplets at each distance.

43. A computer program product comprising a computer readable storage medium carrying computer readable program code, for use with an apparatus for fabricating an array of features which apparatus includes a drop deposition unit and a sensing element, the program code when loaded into the computer performing the steps of:

- (a) for each of multiple addresses, dispensing droplets carrying the biopolymers or biopolymer precursors from a drop dispensing unit onto the substrate, so as to fabricate the array;
- (b) detecting electrical signals resulting from dispensed droplets striking a sensing element during step (a);
- (c) evaluating a performance characteristic of the apparatus based on the detected signals; and

US Application No. 09/558,532

ATTY DOCKET NO. 10990616-1

Page 9

(d) when an error is detected in which an evaluated performance characteristic is outside a predetermined tolerance then, prior to causing the drop dispenser to dispense droplets onto that same substrate, activating an operator alert or operating the apparatus so as to correct for the error before, or compensate for the error during, dispensing of other of the droplets onto that same substrate.

44. (PREVIOUSLY AMENDED) A computer program product comprising a computer readable storage medium carrying computer readable program code, for use with an apparatus for fabricating an array of features which apparatus includes a drop deposition unit and a sensing element, the program code when loaded into the computer performing the steps of:

- (a) for each of multiple addresses, dispensing droplets carrying the biopolymers or biopolymer precursors from a drop dispensing unit onto the substrate, so as to fabricate the array;
- (b) dispensing droplets toward the sensing element after the dispensing of some droplets onto the substrate;
- (b) detecting electrical signals resulting from dispensed droplets striking a sensing element during step (b);
- (c) evaluating a performance characteristic of the apparatus based on the detected signals; and
- (d) when an error is detected in which an evaluated performance characteristic is outside a predetermined tolerance, identifying one or more features on the array which are defective as a result of the error.